



RP735-R Media Player

More Power in a Small Package!

Based on the proven and excellent RP735-R, an alternative ruggedized version is now available from EnQii. It remains one of the smallest and most powerful digital signage appliances in the world and is housed in a more rugged steel casing. At a small 6 ½ x 6 x 1 ¾ inches, this tiny device matches the capabilities of its sibling, including playing HD video up to 1080p, Flash and multizone display. Additionally, it provides two VGA outputs and an RS232 serial port for connection to a display panel.

When used with EnQii's market-leading RemoteTransfer™ software, more options are unlocked including RSS feeds, multizone display and panel controls via RS232 control.

With the RP735-R's small size and weight, this device can be installed anywhere. It will fit neatly behind a display panel, or discretely in a ceiling void or rack, and it has more flexible bracket options. Combined with its low power consumption and rugged casing, the RP735-R is ideally suited for the toughest of jobs.

The RP735-R from EnQii complements our Remote Transfer™ software to create a robust and scalable digital signage solution. As a dedicated digital signage appliance designed to perform to the highest standards of operation and hours, you can be certain that your content will always be showing!

For a demonstration of EnQii's powerful and flexible digital signage solutions, please contact your local office or visit: www.enqii.com/contact/

| PLAYERS | RP400 | RP735 | RP735-R | RP740 |
|---|--|--|---|--|
| Functionality |  |  |  |  |
| Video Formats | MPEG1, 2 & 4 (AVI, QT, DIVX, XVID) | MPEG1, 2 & 4 (AVI, QT, DIVX, XVID) | MPEG1, 2 & 4 (AVI, QT, DIVX, XVID) | MPEG1, 2 & 4 (AVI, QT, DIVX, XVID) |
| Hi-Def | No | Yes – Up to 1080i | Yes – Up to 1080i | Yes – Up to 1080i |
| Flash | Simple only. No Actionsript | Yes. Including Flash 8 & AS2 | Yes. Including Flash 8 & AS2 | Yes. Including Flash 8 & AS2 |
| Audio Types | MPEG2, MP3 | MPEG2, MP3 | MPEG2, MP3 | MPEG2, MP3 |
| Picture Types | JPEG, BMP, GIF | JPEG, BMP, GIF | JPEG, BMP, GIF | JPEG, BMP, GIF |
| Resolutions | Up to 1368 x 720 | Up to 1920 x 1080 | Up to 1920 x 1080 | Up to 1920 x 1080 |
| Split-Screen | Yes | Yes | Yes | Yes |
| Display Connectivity | VGA | DVI | VGA | VGA |
| Size (inches)(mm) | 7(W)x2.25(H)x9.5(D) 180(W)x57(H)x237(D) | 6.49(W)x1.96(H)x6.49(D) 165(W)x50(H)x165(D) | 6.54(W)x1.89(H)x6.18(D) 166(W)x48(H)x157(D) | 12.5(H)x3.6(W)x13.4(D) 316(H)x93(W)x340(D) |
| Weight | 1.13kg / 2.49lbs (N.W.) | 1.45kg / 3.2lbs (N.W.) | 1.22kg / 2.68lbs (N.W.) | N/A |
| Temperature Sensor | Yes | Yes | Yes | Yes |
| Hardware Watchdog | Yes | Yes | Yes | Yes |
| Expansion Capability (Non-standard Supply) | No | Wi-Fi or TV Tuner card | Wi-Fi or TV Tuner card | Wi-Fi, upgraded video card, TV Tuner card |

About RemoteTransfer™

RemoteTransfer is a world-leading, state-of-the-art content distribution and content management system for out-of-home digital media applications. Whether you are a media owner, retailer, or distributor, RemoteTransfer enables you to efficiently and reliably manage large networks of remote digital signage players and displays. Internet based, it provides easy management of very large networks, from player and network management, real-time monitoring and content distribution to media scheduling, play reporting and historical performance analysis. Visit www.enqii.com for more information.